

فناوری اطلاعات ایران [www.tjpro.ir](http://www.tjpro.ir)

### IP Configuration

- DHCP
- Static

IP Address	<input type="text" value="192.168.1.2"/>
Subnet Mask	<input type="text" value="255.255.255.0"/>
Default Gateway	<input type="text"/>
DNS Server	<input type="text"/>



Web Browser

WEB & DNS Server

Physical Config Desktop Software/Services

**GLOBAL**

Settings

Algorithm Settings

**SERVICES**

HTTP

DHCP

TFTP

DNS

SYSLOG

AAA

NTP

EMAIL

FTP

**INTERFACE**

FastEthernet

HTTP

HTTPS

On  Off

On  Off

File Name: index.html

```
<html>
<center><font size='+2'
color='blue'>Network.Itpro.ir</font></center>
<hr>Welcome to ITPRO.ir
<p>Quick Links:
<br><a href='helloworld.html'>A small page</a>
<br><a href='copyrights.html'>Copyrights</a>
<br><a href='image.html'>Image page</a>
<br><a href='image.jpg'>Image</a>
</html>
```

Page: 1/3

< > + X

ITPro.ir - انجمن تخصصی فناوری اطلاعات ایران





192.168.1.10




Physical Config Desktop Software/Services

### IP Configuration

DHCP  
 Static

IP Address: 192.168.1.10  
Subnet Mask: 255.255.255.0  
Default Gateway:   
DNS Server: 192.168.1.2

 **Web Browser**  
 **Cisco IP Communicator**

 **E Mail**       **PPPoE Dialer**       **Text Editor**

ITPro.ir - انجمن تخصصی فناوری اطلاعات ایران



192.168.1.20

Physical

Config

Desktop

Software/Services

## Command Prompt

```
Packet Tracer PC Command Line 1.0
PC>ping 192.168.1.2

Pinging 192.168.1.2 with 32 bytes of data:

Reply from 192.168.1.2: bytes=32 time=9ms TTL=128
Reply from 192.168.1.2: bytes=32 time=9ms TTL=128
Reply from 192.168.1.2: bytes=32 time=8ms TTL=128
Reply from 192.168.1.2: bytes=32 time=9ms TTL=128

Ping statistics for 192.168.1.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 8ms, Maximum = 9ms, Average = 8ms

PC>
```

